

PRODUCT-DETAILS

T7L 1000 PR231/P I In=1000A 4p F F M

T7L 1000 PR231/P I In=1000A 4p F F M



Algemene informatie

Type	T7L 1000 PR231/P I In=1000A 4p F F M
Artikelnummer	1SDA062825R1
EAN	8015644653743
Omschrijving	T7L 1000 PR231/P I In=1000A 4p F F M
Omschrijving	C.BREAKER TMAX T7L 1000 FIXED FOUR-POLE WITH FRONT TERMINALS AND STORED ENERGY OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC PR231/P-I R 1000

Ordering

EAN	8015644653743
Minimale bestelhoeveelheid	1 stuk
Nummer douanetarief	85362090

Dimensions

Product netto breedte	280 mm
Product netto hoogte	268 mm
Product netto diepte	178 mm
Product netto gewicht	14 kg

Container Information

Pakketniveau 1 Units	1 stuk
Pakketniveau 1 Breedte	360 mm
Pakketniveau 1 Hoogte	350 mm
Pakketniveau 1 Lengte	360 mm
Pakketniveau 1 Brutogewicht	15.5 kg
Pakketniveau 1 EAN	8015644653743

Environmental

RoHS-status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Additional Information

Elektrische duurzaamheid	2000 cycle 60 omwentelingen per uur
Mechanische duurzaamheid	10000 cycle 60 omwentelingen per uur
Aantal polen	4
Vermogensverlies	at Rated Operating Conditions per Pole 30 W
Product hoofdtype	SACE Tmax T
Productnaam	Moulded Case Circuit Breaker
Producttype	CB
Toegekende stroom (I_n)	Main Circuit 1000 A
Nominale impuls grensvoltage (U_{imp})	8 kV
Nominaal isolatievoltage (U_i)	1000 V
Nominaal bedrijfsvoltage	690 V AC
Nominaal vermogen kortsluitvermogen (I_{cs})	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 120 kA (400 V AC) 120 kA (415 V AC) 120 kA (440 V AC) 100 kA (500 V AC) 64 kA (690 V AC) 37.5 kA
Nominale kortstondige grensstroom (I_{cw})	for 1 s 20 kA
Nominaal ultiem kortsluitvermogen (I_{cu})	(220 V AC) 200 kA (230 V AC) 200 kA (380 V AC) 120 kA (400 V AC) 120 kA (415 V AC) 120 kA (440 V AC) 100 kA (500 V AC) 85 kA (690 V AC) 50 kA
Nominale ononderbroken stroom (I_u)	1000 A
Uitgave	PR231/P-I
Uitgavetype	EL
Kortsluitingsprestatieniv eau	L
Normen	IEC
Subtype	T7
Geschikt voor	T7M
Geschikt voor productklasse	Moulded Case Circuit Breakers
Terminalverbindingstype	Fixed Circuit-Breakers Front

Versie

F

Certificates and Declarations (Document Number)

Gegevensblad, technische informatie	1SDC210015D0201
Conformiteitsverklaring - CE	9AKK106713A5537
Milieu-informatie	9AKK10103A1059
GL-certificaat	1SDL000163R0054
Instructies en handleidingen	1SDC210015D0201
REACH Declaration	9AKK108466A1425
RoHS-informatie	9AKK108466A1424

Classifications

ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC000228 - Vermogensautomaat
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object classificatiecode	Q
UNSPSC	39120000
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categorieën

Laagspanningsproducten en -systemen → Vermogensschakelaars → Gesloten vermogensschakelaars → Tmax gesloten vermogensschakelaars

